

Description	Wanderer 40
Standar model	
General Data	Fibreglass centreboard cutter , classic design
Design	Martin Bekebrede
L.o.a	13,10 m
L.o.d.	12,10 m
Width	3,95 m
Draft	0,85 / 2,25 m
Displacement	12500 kg , ballast 3700 kg steel punchings embedded in polyester
Sail area	94 m2
Engine	Nanni 50 Hp diesel
Certification	CE-A
Construction :	
Romp	hand layup GRP standard colours black or nightblue underwater part is treated with Gelshield epoxy, finished with International antifouling and white waterline 2x ships name and 1x homeport on vinyl included ballast : steel pellets in bilge area , imbedded in GRP.
Superstructure:	sandwich structure, plywood inlay , standard colour ivory Other colours OPTIONAL
Stainless parts	bollards, shroudsupports, rudderfittings, centreboard shaft, mastsupport bowsprit withsupport, 8 portholes and 8 windowframes, stainless pulpits and twin-wire railing, including 3 gates
stainless tanks	Fresh water 500 L , Diesel 180 L , Wastewater 130 L aluminium escape hatch
OPTIONAL	aft window, extra front windows, extr portholes fixed-tube railing.
Woodwork :	
Exterior :	Entrance doors and sliding hatch : teak untreated Flexiteek on cockpit seats and floor varnishing / oiling OPTIONAL
OPTIONAL	Flexiteek combing all around the hull full Flexiteek decking all in real teak (price on demand)
Interior :	see interior plan : Standard wood : beech or mahogany OPTIONAL : cherry, light oak
	Specifications : Inside of hull insulated with poly-urethane sheets against condensation Ceilings, walls and bulkheads of GRP-plated plywood. Floor of solid iroco on plywood. Lockers, kitchen and furniture of marine plywood with beech /mahogany veneer lists, plints, workt
Conservation	Exterior wood untreated , oil or varnish OPTIONAL Interior : wooden parts varnished satینگloss polyurethane plywood parts painted off-white Floor oiled.
Technical :	
Engine	Nanni 50 Hp diesel, stainless propshaft, brass propellor, panel and morsecontrol

Centreboard control	Handhydraulic control : manual pump, cylinder and position indicator.
Electrics	12V system : 80 Ah starterbattery, 2x140Ah servicebattery, separation relay. switchpanel with fuses and switches ; tanklevelmeters and voltmeter LED-lighting in ceilings, readinglamps (chrome / stainless) 3-colour/anchor light in mast, red/green in bow. Bilgepumps : 2x electric bilgewatch 2x manual pump shorepower connection with 25 A charger, cable and 4x 220V socket
Galley	gascooker with oven running water (hot and cold) in kitchen and toilet ; stainless sinks
Toilet	coolbox 60 L with compressor or 65L electric refridgerator Manual pumptoilet with odourfilter, wastewatertank . Electric toilet OPTIONAL
Anchor	Galvanised M-anchor 20kg , electric anchorwinch, 50 m chain and chainlocker
Instruments OPTIONAL	Standard : compass, logg/echosounder radio / cd , solar panel, autohelm, GPS-plotter, VHF, windmeter, etc. bowthruster 85 kgf, hot air heater Eberspächer 5 kW , etc.
Rigging :	standard : cutterrigger with aluminium mast and boom, selftacking jib 2x Harken St50.2 selftailing winches for genoasheets, 1x St35.2 and 1x St 20 for mainsail and reef handling. Stainless shrouds and spanners , stoppers on cabin roof All halyards and sheets controlled from cockpit.
General :	CE-A certificate and owners'manual Matrasses and cushions for seats with cover from standard collection 4 fenders , 4 mooring lines 2 Fire extinguishers folding bathing ladder 6 steps
OPTIONAL	cockpitcover, cushions, table etc. see pricelist./ optionslist